ISSN 3042-254X (Online)

JOURNAL OF UUNT: INFORMATICS AND COMPUTER SCIENCES

VOLUME 1
ISSUE 1
2024

http://juuntics.unt.edu.rs

ISSN xxxx-xxxx (Online)

Journal of UUNT: Informatics and Computer Sciences

Volume 1, Issue 1, December 2024.

http://juuntics.unt.edu.rs

IMPRESSUM

Journal of UUNT: Informatics and Computer Sciences

(Volume 1, Issue 1, December 2024)

Editor in chief:
Prof. dr Lazar Stošić

Publisher:
Faculty of Informatics and Computer science,
University Union—Nikola Tesla, Belgrade
Address: Cara Dušana 62-64, 11158 Belgrade
Phone: + 381 11 2180-271

http://juuntics.unt.edu.rs/
E-mail: lstosic@unt.edu.rs

For publisher:
Zvonko Božilović

CONTENTS

Mobile robotic laboratory - UNT Lab

Olja Krčadinac, Željko Stanković, Sanja Mrazovac, Lazar Stošić.....1-10

Genetic Chip Technology and Applications

Dragana Đokić, Vladimir Đokić, Željko Stanković, Dalibor Drljača, Siniša Tomić.....11-17

The Application of Deep Learning in Medicine: Benefits, Challenges, and Future Prospects

Nebojša Stojaković, Olja Krčadinac.....19-25

UDC:
xxx
xxx
10.62907/juuntics240101001k

Mobile robotic laboratory - UNT Lab

Olja Krčadinac[1], Željko Stanković[1], Sanja Mrazovac[2], Lazar Stošić[1]*

[1]University "Union – Nikola Tesla", Faculty of Informatics and Computer Science, Belgrade, Serbia
E-mail: okrcadinac@unionnikolatesla.edu.rs, zstankovic@unionnikolatesla.edu.rs, lstosic@unt.edu.rs
[2]University "Union – Nikola Tesla", Faculty of Ecology and Environmental Protection, Belgrade, Serbia
E-mail: smrazovac@unionnikolatesla.edu.rs

Check for updates

Abstract: The project envisages the creation of an experimental concept of a self-propelled laboratory - UNTLab. In crisis situations, it is necessary to examine the quality (contamination) and composition of the air (soil) in a room or on an open field. The UNTLab self-propelled platform, which was implemented at UNION Nikola Tesla University, Faculty of Information Technologies, will be used without risking human resources. In the current (first) phase of realization, UNTLab is equipped with ten sensors that provide information on temperature, pressure and air humidity, substrate temperature, gas concentration (carbon oxides, propane C3H8, butane C4H10, ammonia...), intensity of EM and UV radiation as and light intensity. In addition to the sensor group, a high-resolution Wi-Fi camera is also installed. All collected data from the sensor group is recorded on a micro SD card. The platform has an additional possibility related to mobility, it is equipped with mecanum wheels, which enables great maneuverability, which also includes holonomic movement. Control of the UNTLab platform is performed via mobile devices, Android application, bluetooth communication or wi-fi network.

Keywords: *robotic platform, mobile laboratory, mecanum wheels.*

1. INTRODUCTION

UNTLab is an independent robotic platform (Cvetković, & Stanković, 2010) equipped with a camera and a set of sensors. The platform is controlled via a serial communication channel with the Bluetooth system, which is paired with a mobile device. The Android application that controls the UNTLab platform simultaneously displays the data collected from the sensor array on the mobile device. The purpose of the robotic platform is multiple and can be used as:

- Educational tool,
- Mobile measuring module,
- Mobile security system

In addition to its core functionality, the UNTLab platform demonstrates the growing importance of robotics in addressing critical global challenges. By combining advanced sensor technology, robust mechanical design, and user-friendly control via mobile applications, UNTLab offers a versatile solution for real-time data collection and analysis. Its potential extends beyond crisis management, encompassing environmental monitoring, resource management, and educational purposes. The platform serves as a practical example of how modern technology can mitigate risks to human health and safety while fostering innovation in interdisciplinary research and education.

*Corresponding author: okrcadinac@unionnikolatesla.edu.rs

© 2024 by the authors. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

2. ROBOTIZED PLATFORM

The realization of the self-propelled robotic laboratory began with the selection of the platform itself and its construction. We opted for a robust platform with independent suspension and four-wheel drive, Figure 1.

Figure 1: UNTLab platform

Electric motors via reducers drive wheels that can rotate at different speeds and in different directions, which enables the already mentioned holonomic movement (in all directions and directions). The mechanical assembly is elastic and allows the platform to move easily even on unstructured terrain. At the same time, there is enough space to integrate all the modules, sensor group, camera and power components on the platform, leaving enough space for further extensions.The mechanics of the chosen platform allow movement on unstructured terrain. The holonomic movement enabled by the mecanum (Campion et al., 2011; Salih, et al., 2006) wheels provides the great maneuverability UNTLab needs, Figure 2.

Figure 2: Mecanum wheel specific to the UNTLab platform

The specificity of mecanum wheels is the rollers on the wheel surface, placed at an angle of 45º. The wheels can be left and right, they differ in the direction of the rollers and are placed so that all the rollers are directed towards the point of intersection of the diagonals of the platform. A mechanical assembly designed in this way enables a specific holonomic movement. The presented mechanical assembly allows the UNTLab to overcome smaller obstacles and realize more complex maneuvers for the purpose of analyzing its environment.

The next step was defining the components that will be included in the UNTLab system. Key elements such as the sensor group require special attention when locating the sensors on the platform itself. The measurement system was the key component on the basis of which the positioning of the sensors and their fitting with other electronic components was carried out. Figure 3 shows the first working version of the UNTLab platform.



Figure 3: UNTLab platform V10.7

In Figure 4, the system of movement of the platform is shown schematically, i.e. the direction of rotation of each individual wheel. Depending on the direction of rotation of the wheels, we also get the resulting motion of the platform.



Figure 4: Holonomic motion of the UNTLab 3327 platform



Figure 5: Part of the code - control of the operation of individual motors

3. ELECTRONIC COMPONENTS OF THE PLATFORM

All functions of the UNTLab are unified in the pro MEGA microcontroller, shown in Figure 6. The controller allows parallel programming so that we solved all measurement operations with code. We were able to use a large number of sensors because there was no problem in separately monitoring all measurement parameters of each sensor.



Figure 6: Microcontroller Mega Pro

The set of electronic components used on the platform are divided into several groups:
a) control and operation of DC electric motors,
b) communication module,
c) sensor group,
d) sensor shield,
e) video subsystem,
f) energy group.

a) Control and operation of the DC electric motor - is carried out via two modules, (eng. driver) HG7881 which can support the operation of the DC electric motor in load mode up to 2A. That is more than the motors "pull" at the start (single peak is 0.6A). Figure 7 schematically shows the connection of the Uno R3 microcontroller with a system of two HG 7881 modules and DC electric motors (the drive group of the platform).



Figure 7: UNTLab platform powertrain connection

b) Wireless communication with the platform takes place via the new (eng. Bluetooth) module HC06, which has a range of up to 25m, Figure 8.



Figure 8: Connecting the Uno R3 microcontroller to the Bluetooth module HC05

For laboratory experiments it is quite enough. All mobile devices (phones, tablets...) have an integrated Bluetooth module and by installing the UNTLab android application, it is possible to control the platform with a mobile phone and at the same time receive data from the sensor group.

c) Sensor group - it is composed of seven modules. The BMP180 module is a digital sensor and is used to measure air temperature and pressure, Figure 9. The BMP180 sensor can measure pressure in the range of 300 to 1100 hPa (500m-9000m above sea level) and temperature in the range of -40° to 85° with with an accuracy of 1°.



Figure 9: BMP180 module

The second element of the sensor group is the MQ135 module, Figure 10. The sensor is used for the detection of gases harmful to human health such as carbon dioxide, ammonia, sulfur, as well as for the detection of smoke.

Figure 10: Module MQ135

The MQ135 has both analog and digital outputs, with the analog output giving more accurate results and was used in the UNTLab project, Figure 11.



Figure 11: MQ135 connected to the analog input of the microcontroller

It is necessary to calibrate the sensor in order for the results to be accurate. The calibration of the CO2 gas sensor was done in the laboratory premises and the value obtained was a program constant.

The third module is the DHT 11 air humidity sensor, Figure 11a.



Figure 11a: Humidity sensor

The fourth sensor is the UV module S12SD, which is shown in Figure 11b.



Figure 11b: UV sensor S12SD

The fifth module is an IR temperature sensor. In the project, the role of the IR sensor is to measure the temperature of the substrate on which the ROBOLab is placed, figure 11c.

Figure 11c: IR module

The last in the series is the BH1750 light module, figure 11d.

Figure 11d: BH1750 light module

d) Energy group - battery power supply of the UNTLab platform is divided into two segments. The first segment is a 9V battery power supply that ensures reliable operation of the microcontroller, communication module and all sensor modules. The second segment is the battery power supply intended for the motor group and the NANO controller. Two 18650 batteries with a nominal voltage of 3.7V are connected in series (total voltage is 7.4V). With its capacity, the battery block enables continuous movement of RoboLab in a time interval of more than 20 minutes.

4. MEASUREMENT AND READING OF SENSOR VALUES

The program for the microcontroller (programming language C# is used) is divided into four segments:

- Communication part that opens and maintains a two-way Bluetooth channel (module HC06),
- Control elements (drivers) that control the operation of the electric motor,
- Acquisition of data from the protective sensor group,
- Acquisition of data from ambient sensors BMP180 and MQ135, DHT11, BH1750, EMZ and SD125.

Part of the code for communication with Bluetooth module HC06 is shown in Figure 12.

```
SoftwareSerial Bluetooth(2, 3); // TX, RX

if (Bluetooth.available()){ //prijem podataka

  Data=Bluetooth.read();
```

Figure 12: Opening the communication channel

The electric motor is controlled via a module (driver). The signals from the controller are sent to the drivers that control the complete operation of the motor (starting, stopping or changing the direction of rotation). Figure 13 shows the code that activates all four motors. The wheels rotate in the same direction ensuring that the platform moves forward.

```
//------- to move FORWARD ----------------------------
digitalWrite(in1, HIGH); analogWrite(enPD, 248-motorSpeedR);
digitalWrite(in2, LOW); analogWrite(enPL, motorSpeedL);
digitalWrite(in3, HIGH); analogWrite(enZD, motorSpeedL);
digitalWrite(in4, LOW); analogWrite(enZL, 248-motorSpeedR);
```

Figure 13: Part of the code to control the electric motor - forward movement

The BMP180 module is a digital temperature and air pressure meter. The algorithm we used during programming is shown in Figure 14.



Figure 14: Algorithm for the BMP135 sensor

A part of the code that was developed for the purposes of the UNTLab project is shown in Figure 15.

```
//---------------------------------CO2
char status;
  double temp,P,p0,a;

   status = pressure.startTemperature();
  //-------------------------------------

if (status != 0)
  {
    // Cekamo da se merenje zavrsi:
    delay(status);

    status = pressure.getTemperature(temp);
    if (status != 0)
    {
      // Prikazi merenje:
      Serial.print("temperature: ");

      Serial.print(temp);
      Serial.print(" stepeni C, ");
```

Figure 15: Code for temperature measurement

The MQ135 module is a digital gas detection measuring element that was already described in the previous chapter. The code defined for UNTLab is shown in Figure 16. In Figure 17 we have a control listing generated during program testing. The modules must programmatically coordinate with downloading, sending data and controlling the powertrain. Otherwise, the response of the motion control system has a noticeable delay, which is not an acceptable option.

```
    co2now[x]=analogRead(A0);
    delay(20);
}

for (int x = 0;x<10;x++)  //
{
  zzz=zzz + co2now[x];
}

co2raw = zzz/10;
 co2ppm = co2raw - co2Zero;

Serial.print("Vazduh=");
 Serial.print(co2ppm);  //
  Serial.println(" PPM");

//---------------------------------CO2
```

Figure 16: Code MQ135 gas detection measuring element



Figure 17: Listing for gas detection measuring element



Figure 18: Gas detection sensor (taken on development environment V15.9)

5. RECORDING THE ENVIRONMENT

In addition to the sensors whose functions have already been described, the UNTLab is equipped to record all collectign data. The recording set is sent to the mobile device and stored on the micro TF card. One more, RoboLab has a high resolution camera - 1280HD and a coverage angle of 130º. The above characteristics meet the minimum requirements of the UNTLab.

6. PROGRAM FOR REMOTE CONTROL OF UNTLab

In the MIT APP Inventor development environment, the Android code used by the mobile device was written, Figure 19. The development environment allows students to quickly and easily create code using all the advantages of modern technologies.



Figure 19: MIT Invetor, graphical representation of part of the code for a mobile device.

The interface of the UNTLab program, which we use for mobile devices, can be seen in Figure 20.

Figure 20: Android application for managing the robotic platform

7. CONCLUSION

UNTLab can be used in several fields. The first aspect of application that we observe are crisis situations, which are becoming more and more common. The need for a robotic platform of this type is getting bigger and bigger. Encapsulated information collected by UNTLab in a dangerous (contaminated) environment can be of importance in critical situations, without human resources being exposed to danger.

Another aspect of the development of the mentioned platform is in the educational process, as a modern teaching tool. UNTLab represents an excellent ram for further platform development. Through practical examples like this, students are introduced to the world of robotics, mechanics, electronics, and programming the fastest. The projects noticeably increase the students' interest in the mentioned fields, which, through the further development of UNTLab, enables them to become familiar with concepts that are ubiquitous and represent the general trend of implementing new technologies in the syllabi of modern faculties.

The third aspect of the development and application of the platform is of a security nature. The platform can be used as an active security element. According to user requirements and the nature of the purpose of the platform, a suitable set of sensors is also selected. UNTLab, which we have already mentioned, is also equipped with a camera, which further increases the utility value of the platform.

REFERENCE

Campion, G., Bastin, G. and D'AndréA-Novel, B. (2011) Structural Properties and Classification on Kinematic and Dynamic Models of Wheeled Mobile Robots. Russian Journal of Nonlinear Dynamics, 7, 733-769. https://doi.org/10.20537/nd1104002

Cvetković D., Stanković Ž, (2010) Modern programmable educational tools", Conference ITeO 2010, Banja Luka, Republika Srpska, ISBN 978-99955-49-48-0, pp. 181-186

Salih, J.E.M., Rizon, M., Yaacob, S., et al. (2006) Designing Omnidirectional Mobile Robot with Mecanum Wheel. American Journal of Applied Sciences, 3, 1831-1835

https://www.youtube.com/watch?v=Xrc0l4TDnyw

UDC:
xxx
xxx
10.62907/juuntics240101011d

Genetic Chip Technology and Applications

Dragana Đokić[1], Vladimir Đokić[1], Željko Stanković[2], Dalibor Drljača[3], Siniša Tomić[3]*

[1] Doctoral student, University "Union – Nikola Tesla", Belgrade, Serbia,
E-mail: draganadjokic@unionnikolatesla.edu.rs, vladimirdjokic@unionnikolatesla.edu.rs
[2]University "Union – Nikola Tesla", Faculty of Informatics and Computer Science, Belgrade, Serbia,
E-mail: zstankovic@unionnikolatesla.edu.rs
[3]Faculty of Information Technologies, Pan-European Aperion University, Banja Luka, Bosnia and Herzegovina,
E-mail: dalibor.p.drljaca@apeiron-edu.eu, sinisa.m.tomic@apeiron-edu.eu

Check for updates

Abstract: Gene chips are widely used in animal and plant science. Generally, microarrays are of two types, cDNA or oligonucleotide, cDNA was developed at Stanford University, while oligonucleotides were developed by Affymetrix. We will explore genetic chips, the technology used for their production and reading, and their applications. Gene chips, which are becoming increasingly popular throughout the field of molecular biology and biotechnology, are a recently developed technique that provides efficient access to genetic information using miniaturized high-density arrays of DNA or oligonucleotide probes. Both fundamental and applied research benefit greatly from the specific advantages of this method. There are several steps in the design and implementation of DNA chip technology: probe generation, chip fabrication, sample preparation, analysis, readout, and software. At present, the main application of large-scale microarrays is comparative expression analysis. Microarray technology allows for the analysis of expression profiles for thousands of genes in parallel. One of the most significant applications of this technique is gene expression and profiling on a genome-wide scale. Genechip technology is a new technique that will undoubtedly significantly increase the speed of molecular biology research.

Keywords: *Genetic chips, DNA, RNA, biotechnology.*

1. INTRODUCTION

Gene chips are widely used in animal and plant science. Generally, microarrays are of two types, cDNA or oligonucleotide, cDNA was developed at Stanford University, while oligonucleotides were developed by Affymetrix. The construction of cDNA or oligonucleotide helps to compare the gene expression level of treated and control samples by labeling mRNA with green (Cy3) and red (Cy5) dyes. The hybridized gene chip emits fluorescence whose intensity and color can be measured. RNA labeling can be done directly or indirectly. The indirect method involves amino allyl modified dUTP in place of a previously labeled nucleotide. Hybridization of the gene chip generally occurs in the minimum possible volume to ensure the formation of a heteroduplex and ten times more DNA is observed on it. Confocal or semi-confocal laser technologies in combination with a CCD camera are used to acquire images. Genes are used for standardization to detect cDNA gene chips that are not present in treated or control samples. Statistical analysis (image analysis) and cluster analysis software were developed by Stanford University. Gene chip technology has many applications such as expression analysis, gene expression (molecular phenotypes) and regulatory element coexpression. Gene chips, which are becoming increasingly popular throughout the field of molecular biology and biotechnology, are a recently developed technique that provides efficient access to genetic information using miniaturized high-density arrays of DNA or oligonucleotide probes. Both fundamental and applied research have benefited greatly from the specific advantages of this method. Originally developed to enhance the genome sequencing project, the technology has evolved rapidly and has been adapted to a wide range of applications. DNA chips are powerful tools for studying the molecular basis of interactions on a scale that would be impossible using conventional analysis. Recent developments in microarray technology have greatly accelerated research into gene regulation. Arrays are mainly used to identify which genes are turned on or off in a cell or tissue, as well as to assess the level of gene expression under different conditions. This technology has successful ap-

*Corresponding author: draganadjokic@unionnikolatesla.edu.rs

© 2024 by the authors. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

plications for studying the simultaneous expression of thousands of genes and for detecting mutations or polymorphisms, as well as for their mapping and sequencing. We will explore DNA chips, the technology used for their fabrication and reading, and their applications.

2. GENETIC CHIP

The emergence of DNA chips in the second half of the 1990s has become a new biotechnical revolution that is equivalent in importance to the decoding of DNA structures in the 1950s and the investigation of the fundamental laws of molecular genetics, such as the genetic code, and the main assertion of molecular biology in the 1960s, i.e. the discovery of reverse transcription, the creation of the first recombinant constructs in the 1970s and the investigation of enzymatic methods of manipulating genetic material in vitro. This technology has long been has found its way, since the first official meeting of scientists working in this field, held in Moscow in 1991, which was attended by about 50 scientists from Europe and the USA. At that time, the initial goal was to develop a technology for high-throughput sequencing of the human genome, called hybridization sequencing. However, the field has rapidly diversified in its methodology and applications. Today, DNA chips seem to be a common part of biological science. DNA chips have been very successful in various genomic analyses (Debouck C., Goodfellow P., 1999), ranging from SNP (Wang D.G. et all, 1998) detection to functional genomics (Lockhart D.J. et al., 1996). There are different names for chips, such as DNA/RNA chips, Biochip, Genechip or DNA arrays. An array, described as a macroarray, can be defined as an ordered collection of macrodots, or microdots, where each dot contains a single defined type of nucleic acid. Large sets of these nucleic acid probe sequences are immobilized at defined locations on the surface of a substrate capable of accessing large amounts of genetic information from biological samples in a single hybridization assay. Each dot represents the equivalent of a conventional assay performed in a test tube. Dot arrays applied to a biochip reproduce each of these assays several times, up to a total of three or four, thereby increasing the reliability of the assay results. Using the "lock and key principle," complementary hybridization is used in biochip assays. In a typical application, DNA or RNA target sequences are isolated from a biological sample using standard molecular biology protocols. The sequences are fragmented and labeled with detection molecules, and a mixture of labeled sequences ("key") is applied to the array, under controlled conditions, for hybridization with surface probes ("lock"). Sequence complementarity leads to hybridization between two single-stranded nucleic acid molecules, one of which is immobilized on a matrix (Southern E., Mir K., Shchepinov M., 1999). The array is then imaged with a reader to locate and measure the binding of target sequences from the sample to the complementary probe on the array, and software reconstructs the sequence data and presents it in a defined format. In this way, highly parallel DNA hybridization occurs, and assays are possible on miniaturized flat substrates or "chips". There are two variants of chips, in terms of the properties of the aligned nucleic acid sequences of known identity: Format I - cDNA microarrays and Format II - oligonucleotide arrays. Although both cDNA and oligonucleotide chips can be used to analyze gene expression patterns, there are fundamental differences between these methods. Microarrays are subsequently exposed to a labeled sample, hybridized, and largely determine the complementary sequences. Furthermore, there are two basic approaches to creating gene chips. Historically, the first approach was to deposit pre-synthesized oligonucleotides or cDNA fragments onto the chip. The second approach was in situ synthesis using photolithography or piezoelectric printing, which uses technology similar to inkjet printing.

The study of gene expression based on hybridization of mRNA to high-density arrays of immobilized target sequences that can correspond to specific genes is called gene chip technology. cDNA gene chips were developed by Patrick Brown and Ronald Davison at Stanford University (Schena M. et al., 1996). The system is based on standard transcription and PCR amplification followed by cloning of the cDNA for each gene of interest. The cDNA clones are then generally "cloned" onto glass slides, printing technologies have been developed that allow printing of 100,000 clones on a single slide, this system allows for custom arrays (Rose D., 2000). mRNA obtained from biological samples is reverse transcribed and end-labeled using a fluorescent (or occasionally radioactive) laser labeled with nucleotides and hybridized to the array. The fluorescence or radioactive emission from each "spot" is proportional to the relative abundance of a specific transcript in the cDNA pool hybridized to the cDNA spot. The high abundance of the specific transcript in the sample is compared to the high abundance of that transcript in the control sample. This technique, although laborious, provides a fully customizable high-density system with high detection specificity. Oligonucleotide gene chips were developed by Fodor et al. (1991) and Lipshutz et al. (1995). In these systems, oligonucleotide probes are directly synthesized on a solid surface using chemical synthesis supported by lithophotographic techniques. Originally, this strategy was developed to detect DNA single nucleotide polymorphisms (SNPs) (Lipshutz R.J. et al., 1995). It was later applied to measure

mRNA expression. In Affymetrix Arabidopsis arrays, each gene is represented on oligonucleotide probes, while in the central part of the probe, a base is usually replaced by a complementary one. The probe sequences obtained in most cases cover the 3' parts of the coding sequence to increase the sensitivity of the test and the accuracy for SNPs. The RNA obtained from the biological samples is processed before hybridization. Double-stranded cDNA is obtained from total or mRNA (treated) using reverse transcription. cRNA is then obtained using in vitro transcription with biotinylated nucleotides, and then the fragment is hybridized to an oligonucleotide array. If the biotinylated nucleotides are used to synthesize cRNA, the array is visualized by staining with a streptavidin-phycoerythrin conjugate. A value is calculated for the expression of each gene based on the fluorescence derived from each part of the probe.

3. INTEGRATED CIRCUIT TECHNOLOGY

An integrated circuit (IC), also known as a chip or microchip in electronics, is an electronic circuit built on a semiconductor substrate, usually one of the crystals of which is silicon. The circuit is packaged in a hermetically sealed box or non-hermetic plastic capsule, with leads extending from it to the input, output, and power connections, as well as to other connections that may be necessary when the device is put into use. There are also different scales of integration of such circuits. In the case of very large-scale integration, an IC can contain more than 1000 transistors. Intel founder Gordon Moore observed that the number of transistors per semiconductor chip doubles every 18-24 months. Current microprocessor chips (used in personal computers) contain more than 100 million transistors, each a few square centimeters in size. Such a huge degree of integration, which has almost reached the limits of manufacturing technology, helps modern computers to be very fast, compact and relatively inexpensive. A comparable phenomenon has been observed in molecular biology. The miniaturization of certain tools suitable for the manufacture of smart and portable devices, the spotted array system, offers the pharmaceutical, biotechnology and agricultural industries more efficient and economical solutions. DNA microarrays built using photolithography were on a similar path to integrated circuits. In 1998, the Affimetric array contained fewer than 1000 genes, by 2000 it contained 12,000. In the process of manufacturing biochips, semiconductor materials are widely used and widespread. A semiconductor is a solid material whose electrical conductivity at room temperature is between that of a conductor and that of an insulator. At high temperatures, its conductivity approaches that of metals, and at low temperatures it acts as an insulator. The first materials used for semiconductors were the elements germanium, silicon, and tin. Although other materials can be used, chips are usually manufactured on wafers of single-crystal silicon, i.e. silicon in which the orientation of all the crystals is the same. The manufacturing steps include image formation, impurity doping, photolithography, and packaging. Silicon oxide, also called silicon dioxide, is grown on the surface during the image formation phase. Photolithographic methods are used to selectively remove the oxide from the silicon. A layer of photoresist is added to the oxide layer and then exposed to ultraviolet light through a mask. After exposure, the silicon wafer is developed, a process that removes unwanted oxide areas. Impurities add charge carriers to the silicon, and this process produces the unique electronic properties of the semiconductor. Additional layers of silicon are deposited to create, for example, bipolar transistors.

4. MICROCHIP DESIGN

There are several steps in the design and implementation of DNA chip technology: probe creation, chip fabrication, sample preparation, analysis, readout, and software. Many strategies have been explored for each of these steps.

Microarray fabrication begins with the selection of probes to be printed on the array. In most cases, they are selected directly from databases including GeneBank (Benson D.A. et al., 1997) and UniGene (Schuler G.D. et al., 1996). The two most commonly used types of arrays, Format I and Format II, differ in the size of the arrayed nucleic acids. In Format I, cDNA probes, which are relatively long, DNA molecules (500–5000 bases in length) are immobilized on a solid surface such as a membrane, glass, or silicon chip. The probes are often single-stranded DNA fragments processed using the polymerase chain reaction (PCR). These PCR products are amplified with gene-specific primers generated using chromosomal DNA as a template and then purified by precipitation or gel filtration, or both. Spotting cDNA or PCR products representing specific genes on the array produces DNA arrays. Deposition of a few nanoliters of purified material typically at 100-500 mg=ml generates each spot on the array. Printing is done either by a high-precision robotic system, i.e., by a high-speed robot (array) or by using inkjet technology that spots a sample of each gene product onto a number of matrices in a batch operation or prints. These types of arrays are mainly used for large-scale screening and expression studies. In Format II, an array

of oligonucleotide probes is produced either by in situ light-directed chemical synthesis or conventional synthesis followed by on-chip immobilization . Those with short nucleic acids (oligonucleotides up to 25 nt) are useful for mutation detection and expression monitoring, gene discovery, and mapping.

DNA chip technology has evolved in two main ways. In one method, nucleic acids (previously chemically synthesized oligonucleotides or single-stranded DNA fragments, i.e. cDNA) are immobilized on the surface of a chip in sequence to form capture probes. Using either printing needles or inkjet printing, many copies of the nucleic acid sequence can be attached to the substrate (Figure 1).



Figure 1. Methods for creating DNA arrays (Gabig-Ciminska M.,& Cminski A., 2001)

Contact printing involves wetting a printing stylus with a nucleic acid solution and tapping it onto the surface of the microarray. Inkjet printing ejects uniform droplets of the solution onto the substrate. An alternative, known as in situ fabrication, builds the oligonucleotide sequence at each site one nucleotide at a time. This is done using inkjet or photolithography (Figure 1). Construction of such chips begins with a glass substrate that has been chemically prepared with sites ready for nucleotide binding. In inkjet printing, nucleotide solutions are ejected from a nozzle onto the substrate and then chemically fixed to the surface. The next set of nucleotides is dropped onto the first and chemically fixed. The process is repeated until the desired set of nucleic acids is complete. In photolithography, a photosensitive chemical that is released under illumination closes the sites. Light at 365 nm shines through a patterned mask onto the chip, causing the capping chemical to detach from the areas it hits, revealing the primed sites. A solution containing one of four types of nucleotides (each molecule of which is itself bound to a capping molecule) is then washed over the chip. The nucleotides bind only to the areas that have been exposed and add a capping layer to themselves. Since the process can be repeated with a different mask and a different nucleotide, different DNA sequences can be built on the chip. Multiple probe arrays are synthesized simultaneously on a large wafer. This parallel process improves reproducibility and helps achieve high synthesis rates (Southern, Mir, & Shchepinov, 1999). Production chips can pack 400,000 probes into 20 mm patches. One drawback of the current photolithography method is that a new set of masks must be produced for each new array type. There is a maskless technique that uses an array of micromirrors that reflect to appropriate locations on the chip.

Gene chip sample preparation can be used to measure gene expression levels in a variety of ways. One of the most popular applications of gene chip comparison is to compare gene expression levels in two different samples, e.g. the same cell or cell type under two different conditions. This is based on labeling mRNA extracted from one condition with one dye, e.g. green, and from the other condition with a different dye, e.g. red. The hybridized gene chip is ignited by a laser and scanned at wavelengths suitable for the detection of red and green, as shown in Figure 2.



Figure 2. Microarray: General functional principle

The amount of fluorescence emitted by the laser pulse corresponds to the amount of nucleic acid bound to each spot. If nucleic acid from the sample in state 1 is present in large quantities, the spot will be green, while if nucleic acid from the sample in state 2 is present in large quantities, it will be red. If both are equal, then it will be yellow. If neither is present, it will not fluoresce and will then appear black. The intensity of fluorescence and color for each spot determines the relative expression levels as genes in both samples are expressed and can be assessed. In this way, thousands of data points, each providing information on the expression of a particular transcript, can be obtained from a single experiment. The complexity of gene array analysis means that tissue sampling becomes a crucial factor in the data produced. As gene chips have been used with increasing frequency in recent years, the amount of variation in gene expression between samples, even from the same tissue in the same person, can exist. Precise sampling (including factors such as sampling at the same time of day and month) and the ability to sample homogeneous tissues, using techniques such as laser capture (Simone N.L., et al., 1998) microdissection, are key steps in obtaining accurate analysis. At the same time, the amount of tissue required can be a problem if relatively large amounts of RNA are needed. However, newer techniques have been developed to amplify RNA that allow extraction from small tissue (Hertzberg M., et al., 2001) samples. Brown's group at Stanford University described how a pool of RNA obtained from 11 different human tumor cell lines became a kind of de facto universal human reference RNA. Recently, a labeled oligonucleotide complementary to each function on the array has proven to be an efficient reference, without the complications associated with mRNA-derived references (Dudley A.M. et al., 2002). Ultimately, the development of gene chip technology or other processes that allow for parallel high-throughput measurements of absolute large amounts of RNA are needed to provide robust characterization of transcriptomes of specific cell lineages, developmental stages and diseases.

Expression labeling protocols are based on reverse transcription of mRNA, either from highly purified poly(A) mRNA or total RNA extract. Extensive purification of RNA is necessary to remove all contaminating proteins, polysaccharides and other organic materials, especially RNases. Many protocols developed for high-quality RNA extraction use a variety of in-house and commercial reagents. Initial target labeling protocols, where reverse transcription from mRNA is prepared, used poly(dT) primers in the presence of fluorescently labeled nucleotides, usually cy3- or cy5-conjugated (dCTP or dUTP). Cy3- or cy5-conjugated nucleotides are bulky, however, and their use makes their absorption by standard enzymes very inefficient. In addition, the rate of absorption can vary between dyes, potentially leading to color bias. In an alternative method, an amino allyl modified dUTP is used in place of a pre-labeled nucleotide. After reverse transcription, the free amine group on the amino allyl modifies the dUTP and can be coupled to the reactive N-hydroxysuccinimidyl ester of a fluorescent dye. Although this technique is more time-consuming than direct labeling, its advantages include better sensitivity, less color bias, and reduced cost.

5. ANALYSIS

Although gene chip technology exists, the basic methods of analysis are well established. An image analysis program, in most cases, is used to calculate the quantitative ratio of gene expression levels between the two samples to be compared. Before the software is able to interpret the intensity value for each probe as a grid, it must be superimposed on the gene chip image to map the location of the pixels representing each dot. A software package for initial image analysis was developed at Stanford University and is available to academic users. Most scanners are sold with the option of an image analysis software package such as Imagene (Biodiscovery, Los Angeles, CA, USA) Quantarray (GSI Lumonics) or GenePix 2.0 (Axon instruments, Foster City, CA, USA). Some of these packages use cluster analysis algorithms to group genes in a sequence according to their expression profiles over a number of experiments. A version of this type of program, called Cluster, is also available from Stanford University. Bilban et al. (2002) introduced a method for filtering false positive and false negative DNA gene array experiments. This was achieved by evaluating a set of positive and negative controls by receiver operating characteristic (ROC) analysis. The advantage of this approach is that users can define thresholds based on the sensitivity and specificity of the observations. The area under the ROC curve allows for quality control of gene array hybridization. This method was applied to custom gene arrays developed for the analysis of invasive melanomas where tumor cells were examined with fewer misclassified genes. Provided that appropriate positive and negative controls are included in the set on the gene array, ROC analysis eliminates the problem of arbitrary selection of threshold levels in gene array experiments. The proposed method is also applicable to adapted to commercially available cDNA gene chips and can help improve the predictive reliability of gene chip experiments.

6. CONCLUSION

We can conclude that gene chips are becoming increasingly popular throughout the field of biotechnology. Recently, a technique has been developed that provides efficient access to genetic information, and software development allows for insight into the complete scanned sequence.

The readout of the image from the gene chip is recorded as an image obtained by a scanner for the detection of a fluorescent signal or for the detection of radioactive signals. Scanners currently available use either scanning confocal laser technology or charge-coupled device (CCD) cameras.

More than a decade of rapid progress in biology has swept an avalanche of genetic information among scientists. But the analysis of such a huge number of novelties, leads to the conclusion that studying the inner workings of cells or diagnosing diseases would not be practical without high-throughput technologies, such as DNA microarrays. They allow scientists to search for the presence, production, or sequence of thousands of genes at the same time. Currently, the power and breadth of DNA microarrays have become a dominant factor in genomics, transcriptomics, pharmacogenetics, and biology, while also becoming increasingly important in preclinical research and even clinical studies. Innovative efforts, combining fundamental biological and chemical science with technological advances in the fields of micromachining and microfabrication, should lead to even more powerful devices that will accelerate the realization of large-scale genetic research testing. GeneChip offers extraordinary tools for genetic analysis, appropriate applications for these new devices, and the intellectual contribution that is still needed.

At present, the main application of large-scale microarrays is comparative expression analysis. Microarray technology allows the analysis of expression profiles for thousands of genes in parallel. One of the most significant applications of this technique is gene expression and their profiling on a genome-wide scale. Genechip technology is a new technique that will undoubtedly significantly increase the speed of biotechnology research.

REFERENCE

Benson D.A., Boguski M.S., Lipman D.J., Ostell J. (1997). GenBank. Nucleic Acids Res 25: 1–6.

Bilban M., Buehler L.K., Head S., Desoye G. and Quaranta V. (2002). Defining signal thresholds in DNA microarrays: exemplary application for invasive cancer. BMC Genomics 3:19.

Debouck C., Goodfellow P. (1999). DNA microarrays in drug discovery and development. Nat Genet 21: 48–50.

Dudley A.M., John A., Martin A.S., George M.C. (2002). Measuring absolute expression with microarrays with a calibrated reference sample and an extended signal intensity range. PNAS, USA 99:7554-7559.

Fodor S.P.A., Read J.L., Pirrung M.C., Stryer L., Lu A.T., Solas D. (1991). Light-directed, spatially addressable parallel chemical synthesis. Science 251:767-773.

Gabig-Ciminska M., Cminski A. (2001). An Introduction to DNA Chips. ResarchGete.

Hertzberg M., Sievertzon M., Aspeborg H., Nilsson P., Sandberg G., Lundeberg J. (2001). cDNA microarray analysis of small plant tissue samples using a cDNA tag-target amplification protocol. Plant J. 25:585-591.

Lipshutz R.J., Morris D., Chee M., Hubbell E., Kozal M.J., Shah N., Shen N., Yang R., Fodor, S.P.A. (1995). Using oligonucleotide probe arrays to access genetic diversity. Biotechniques 19:442-447.

Lockhart D.J., Dong H., Byrne M.C., Follettie M.T. (1996). Expression monitoring by hybridisation to high density oligonucleotide arrays. Nat Bitechnol 14: 1675–1680.

McGall G., Labadie J., Brook P., Wallraff G. (1996). Ligh-directed synthesis of high-density oligonucleotide arrays using semiconductor photoresists. Proc Natl Acad Sci USA 91: 5022–5026.

Rose D. (2000). Micro fluidic technologies and instrumentation for printing DNA microarrays. In: Microarray Biochip Technology. Ed. Schena, M., pp.19-38, Eaton Publishing.

Schena M., Shalon D., Heller R., Chai A., Brown P.O., Davis R.W. (1996). Parallel human genome analysis: microarray-based expression monitoring of 1000 genes. PNAS, USA. 93:10614-10619.

Schuler G.D., Boguski M.S., Stewart E.A., Stein L.D. (1996). A gene map of the human genome. Science 274: 540–546.

Simone N.L., Bonner R.F., Gillespie J.W., EmmertBuck M.R., Liotta L.A. (1998). Laser-capture microdissection: opening the microscopic frontier to molecular analysis. Trends Genet. 14:272-276.

Southern E., Mir K., Shchepinov M. (1999). Molecular interactions on microarrays. Nat Genet 21: 5–9.

Southern E., Mir K., Shchepinov M. (1999). Molecular interactions on microarrays. Nat Genet 21: 5–9.

Wang D.G., Fan J., Siao C., Berno A. (1998). Large-scale identification, mapping and genotyping of single-nucleotide polymorphisms in the human genome. Science 280: 1077–1082.

UDC:
xxx
xxx
10.62907/juuntics240101019s

The Application of Deep Learning in Medicine: Benefits, Challenges, and Future Prospects

Nebojša Stojaković[1], Olja Krčadinac[*1]*

[1]University "Union – Nikola Tesla", Faculty of Informatics and Computer Science, Belgrade, Serbia
E-mail: okrcadinac@unionnikolatesla.edu.rs, nebojsastojakovicla@gmail.com

Check for updates

Abstract: Deep learning has emerged as a transformative technology in the field of medicine, offering numerous advantages in the diagnosis, treatment, and management of healthcare. This paper explores the application of deep learning in medicine, highlighting its benefits, challenges, and future prospects. The advantages of deep learning include enhanced accuracy and efficiency in diagnosing medical conditions, automation of administrative tasks, support for personalized and preventive care, and the potential for early disease detection and improved treatment outcomes. However, the use of deep learning in healthcare also presents several challenges, including issues related to data transparency, bias in datasets, integration with existing healthcare systems, and the need for high-quality data. Furthermore, the technology's dependence on specialized expertise and the significant costs associated with its implementation pose additional barriers to widespread adoption. Despite these challenges, the future of deep learning in medicine holds great promise, with potential advancements in clinical decision-making, drug discovery, and healthcare accessibility, particularly in underserved and remote areas. This paper provides an overview of the current state of deep learning in medicine and discusses its implications for the future of healthcare.

Keywords: *Artificial Intelligence (AI), Deep Learning, Disease Prediction, Healthcare.*

1. INTRODUCTION

The integration of artificial intelligence (AI) into healthcare has revolutionized the way medical professionals approach diagnostics, treatment, and patient care. Among the most promising AI technologies, deep learning (DL) stands out for its ability to analyze vast amounts of complex data, such as medical images, patient records, and genetic information, with remarkable accuracy. By leveraging neural networks, deep learning systems can identify patterns and make predictions that would be challenging for humans to detect, enabling faster and more accurate diagnoses, personalized treatment plans, and better management of healthcare resources.

In recent years, the application of deep learning in medicine has gained significant attention, as it demonstrates the potential to enhance patient outcomes, reduce human error, and optimize operational efficiencies in healthcare institutions. From medical imaging and disease prediction to drug discovery and telemedicine, deep learning's impact on the medical field is broad and transformative. However, while deep learning presents substantial benefits, its adoption also brings several challenges, including the need for large datasets, the risk of bias, and concerns over the transparency and accountability of AI-driven decisions.

This paper explores the advantages, challenges, and future potential of deep learning in medicine, providing a comprehensive overview of its role in the evolving landscape of healthcare. Through this analysis, we aim to better understand how deep learning is reshaping medicine and the hurdles that need to be addressed for its optimal integration into clinical practice.

2. BENEFITS OF DEEP LEARNING IN MEDICINE

Deep learning has the potential to significantly enhance various aspects of healthcare, offering numerous benefits across different medical domains. These benefits are not only limited to improving the quality of care, but also extend to streamlining medical processes, increasing efficiency, and reducing the

*Corresponding author: okrcadinac@unionnikolatesla.edu.rs

© 2024 by the authors. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

burden on healthcare professionals. The following points highlight the primary advantages of applying deep learning in medicine:

1) Accuracy and Efficiency

Deep learning algorithms are capable of analyzing large volumes of medical data with high accuracy. Whether it's processing medical images, electronic health records, or genomic data, deep learning models can identify subtle patterns and make predictions that often surpass human experts in precision (Li, Zhang, & Zhu, 2023). This reduces the likelihood of diagnostic errors and allows for faster and more reliable medical decision-making.

2) Automation of Repetitive Tasks

One of the significant advantages of deep learning is its ability to automate administrative tasks, such as billing, scheduling, and patient record management. Additionally, deep learning algorithms are being increasingly used to automate tasks like interpreting medical images (e.g., X-rays, MRIs), analyzing lab test results, and even diagnosing diseases. This automation reduces the time required for processing and enables healthcare professionals to focus more on direct patient care (Prabhod, 2024).

3) Support for Healthcare Professionals

Deep learning acts as a decision-support tool, providing medical professionals with valuable insights based on large datasets (Johnson, i drugi, 2016). By identifying complex relationships in patient data, deep learning systems help clinicians make better-informed decisions. While these systems provide support, they do not replace human expertise but rather augment it, allowing doctors to deliver more accurate diagnoses and personalized treatment plans.

4) Personalized and Preventive Healthcare

Deep learning can analyze genetic data, medical history, and lifestyle factors to provide tailored healthcare solutions. This personalized approach is particularly beneficial in fields such as oncology, where treatments can be customized based on individual genetic profiles. Furthermore, deep learning models can assist in predictive analytics, allowing for early detection of diseases and the development of preventive measures for patients at risk (Kalusivalingam, Sharma, Patel, & Singh, 2021).

5) Predictive Capabilities and Early Detection

Deep learning models are instrumental in predicting the onset of diseases and detecting abnormalities in early stages. This can lead to earlier interventions and better control over the patient's condition. For instance, deep learning algorithms can analyze patterns in patient data to predict the likelihood of chronic disease development, enabling timely preventive measures to be taken (Hider, Nasiruddin, & Al Mukaddim, 2024).

6) Improved Access to Healthcare

In remote or underserved regions, access to quality healthcare can be limited. Deep learning-based systems can assist in overcoming these barriers by enabling healthcare providers to remotely analyze medical data, such as imaging scans or patient histories, without requiring physical presence. This advancement is particularly valuable in rural areas or during global health crises, like the COVID-19 pandemic, where telemedicine and AI-powered diagnostics have played a crucial role (Bhattacharya, i drugi, 2021).

7) Ongoing Learning and Education

Deep learning systems can continuously learn from new research, clinical guidelines, and medical literature. By analyzing the latest publications and clinical findings, these systems help healthcare professionals stay updated with the most current knowledge and best practices, ultimately improving patient care (Alowais, i drugi, 2023).

8) Discovery of New Biomarkers

Biomarkers are essential for early disease detection and determining treatment efficacy (Pepe, i drugi, 2001). Deep learning can process vast amounts of genetic and biological data to discover new biomarkers that may be critical for diagnosing previously undetectable conditions or evaluating responses to treatments.

9) Improved Treatment Outcome Predictions

Deep learning models can predict the outcomes of various treatment plans, helping healthcare providers choose the most appropriate therapy for patients. In the context of chronic diseases such as cardiovascular diseases, diabetes, and cancer, these predictions are particularly valuable in optimizing treatment strategies and improving long-term patient outcomes (Zhang, Shi, & Wang, 2023).

10) Remote Monitoring and Telemedicine

AI-powered systems, including wearable devices and sensors, allow for continuous monitoring of patients with chronic conditions or post-operative needs. These technologies can collect data on vital signs, chronic disease progression, and recovery, enabling timely interventions without the need for pa-

tients to visit healthcare facilities (Bhambri & Khang, 2024). During health crises like COVID-19, AI-driven telemedicine solutions have proven essential in providing medical consultations and monitoring from a distance.

11) Advancement in Research and Drug Discovery

Deep learning has made significant strides in accelerating research and drug discovery processes (Dara, Dhamercherla, Jadav, Babu, & Ahsan, 2022). By analyzing large datasets of research studies, clinical trials, and biological data, deep learning algorithms can identify patterns those human researchers might overlook. This capability has been instrumental in discovering new drugs for diseases like cancer and malaria and understanding complex conditions such as Alzheimer's disease (Vatansever, i drugi, 2021).

3. CHALLENGES AND LIMITATIONS OF DEEP LEARNING IN MEDICINE

While deep learning holds great promise for transforming healthcare, its application in medicine is not without challenges and limitations that must be addressed for its successful integration into clinical practice. One of the primary challenges is the quality and availability of data. Deep learning models require large, high-quality datasets for training, and in medicine, access to sufficient, diverse, and well-labeled data is often limited. Medical data can be incomplete, noisy, or inconsistent, which can lead to biased or inaccurate predictions. Furthermore, obtaining datasets that represent diverse patient populations is crucial to ensure that AI models generalize well across different demographic groups.

Another significant concern is data privacy and security. Medical data is highly sensitive, and the use of deep learning in healthcare must comply with strict regulations such as the Health Insurance Portability and Accountability Act (HIPAA) and the General Data Protection Regulation (GDPR). These regulations are designed to protect patient privacy, and their implementation can complicate the collection, sharing, and use of medical data for AI training. Additionally, the risk of data breaches and unauthorized access to sensitive patient information remains a critical issue.

Interpretability and transparency of deep learning models present another major hurdle. Many deep learning algorithms operate as "black-box" systems, making it difficult to understand the reasoning behind their predictions. In medicine, clinicians must understand how a model arrives at a particular diagnosis or recommendation to trust and effectively use it in practice. The lack of transparency can hinder the adoption of AI-driven tools in clinical settings, where decision-making often requires a clear explanation of the rationale behind each recommendation.

Regulatory and ethical challenges also play a critical role in limiting the widespread use of deep learning in healthcare. There is a lack of comprehensive regulatory frameworks in many countries regarding the approval and deployment of AI technologies in medicine. This creates uncertainty for healthcare professionals and technology developers alike. Ethical issues surrounding patient consent, data ownership, and accountability for AI-driven decisions also need to be carefully considered. If an AI system makes a wrong diagnosis, it is often unclear who should be held responsible—the healthcare provider, the AI system developer, or the system itself.

Deep learning models are also prone to overfitting, especially when trained on small or non-representative datasets. Overfitting occurs when a model becomes too tailored to the training data and performs poorly on new, unseen data. In healthcare, this is particularly problematic, as the population is diverse, and clinical contexts can vary significantly. Models that work well for one population or setting may not generalize effectively to others, leading to unreliable outcomes in real-world applications.

The computational and infrastructure requirements for training deep learning models are another limitation. These models demand substantial computing power, often requiring the use of high-performance computing resources such as GPUs or cloud-based systems. This can be a barrier for smaller healthcare organizations or those in resource-limited settings, as the costs associated with acquiring and maintaining the necessary infrastructure may be prohibitive.

Bias and fairness in AI systems are also critical issues in the context of healthcare. Deep learning models can learn and perpetuate biases present in the data they are trained on. If a dataset underrepresents certain demographic groups, the model may perform poorly for those populations, resulting in inequitable healthcare outcomes. Ensuring that AI models are fair and unbiased requires careful selection of training data and thorough validation processes to prevent discriminatory results.

The integration of deep learning into clinical workflows can also present challenges. Healthcare environments are complex, and introducing AI-driven tools requires careful planning to ensure that these technologies fit seamlessly into existing practices. AI systems must be user-friendly, compatible with current medical software, and capable of providing real-time insights without overwhelming healthcare pro-

fessionals with unnecessary information.

Despite the potential of deep learning in medicine, resistance from healthcare professionals remains an obstacle. Many clinicians are skeptical about relying on AI-driven solutions, citing concerns over the reliability of the technology, its potential impact on their decision-making autonomy, and the risk of errors. Building trust in AI systems requires transparent communication about the technology's capabilities, limitations, and the role of healthcare providers in overseeing AI-driven decisions.

Lastly, deep learning models need continual updating and retraining to remain effective. The medical field is dynamic, with new knowledge, emerging diseases, and evolving clinical practices. Keeping AI models up to date requires significant resources and ongoing monitoring. If not regularly updated, models can become outdated and provide recommendations that no longer align with current medical standards.

4. FUTURE OF DEEP LEARNING IN DISEASE PREDICTION

The future of deep learning in disease prediction is promising, as this technology continues to advance and find new applications in medical research and clinical practice. It has the potential to dramatically change the way diseases are treated and diagnosed. Below are some of the main perspectives.

4.1. Development of hybrid models and transfer learning

These are two important concepts used to improve model performance in deep learning. They are crucial when models need to be adapted to new domains or when limited data is available.

4.1.1. Hybrid Models

These models combine multiple approaches or techniques to solve a problem, leading to better results than using just one methodological framework. They integrate different types of algorithms, such as:

- Combination of traditional and deep models: To leverage the strengths of both approaches, traditional machine learning methods (SVM, Random Forest) are combined with deep networks.
- Ensemble models: Techniques like bagging, boosting, and stacking are used to combine multiple models, improving prediction accuracy and reducing variance.
- Combination of different deep network layers: Integrating CNN and RNN in models for video data analysis, where both spatial and temporal information need to be processed.
- Feature extraction layers: Pretrained CNNs are used for image feature extraction, which is then fed into a classification layer based on traditional models.

4.1.2. Transfer Learning

This method allows models to transfer knowledge gained from one task to another similar task. It is especially useful in deep learning due to the complexity of models and large data requirements. Principles of transfer learning include:

- Pretrained models: Models pretrained on large datasets (e.g., ImageNet for images) are fine-tuned on smaller datasets.
- Model adaptation: Adapting a model to new tasks or classes by reworking the final layers or adding new ones. Categories of transfer learning include:
- Inductive Transfer Learning: The target task is similar, and improvements on the source task are expected to improve performance on the target task.
- Transductive Transfer Learning: In new domains, there are few target data but plenty of data from the source domain.

4.1.3. Advantages and Applications of Hybrid Models and Transfer Learning

The advantages include increased efficiency, reduced data requirements, and robustness (hybrid models show greater resistance to overfitting due to their combination of approaches). Applications include:

- Natural Language Processing: Using transfer learning to adapt transformer-based models (BERT, GPT) to specific languages or domains.
- Computer Vision: For image classification, pretrained CNN models are used in industrial or medical applications.

• Healthcare: Using data from similar clinical studies to train disease prediction models on small patient datasets.

Hybrid models and transfer learning represent powerful tools in the field of deep learning, enabling practitioners and researchers to more effectively utilize available data.

4.2. The role of deep learning in personalized medicine

Also known as precision medicine, personalized medicine focuses on tailoring therapeutic and diagnostic procedures to the individual characteristics of each patient. Deep learning contributes to personalized medicine in various ways:

• Big Data Analysis: Enables efficient analysis of data from various sources (genetic information, clinical data, images, lab tests). Advanced algorithms can automatically identify relevant information and patterns from high-dimensional data, aiding clinicians in understanding complex disease patterns.

• Genomic Analysis: Based on genetic variations, deep models like convolutional and recurrent neural networks are used to predict disease predispositions and analyze genetic data. By understanding genetic predispositions, doctors can recommend therapies with fewer side effects and greater effectiveness.

• Diagnostics: In radiology, deep learning models are used to analyze medical images (CT, MRI, X-rays), automatically identifying diseases and abnormalities, improving diagnostic accuracy and speeding up decision-making. Using data from electronic health records, deep learning models can predict diseases before symptoms appear, enabling timely intervention.

• Treatment Personalization: Helps identify the most effective medications and dosages for patients based on their genetic information and responses to previous treatments. By analyzing data from previous patients, models can predict which patients are likely to experience certain side effects, allowing for therapy adjustments.

• Disease Monitoring and Management: Deep learning is used to analyze data collected through wearable technologies (smartwatches, fitness bands), enabling continuous health monitoring and timely alerts. Personalized treatment plans can be developed by analyzing health data and lifestyle factors (physical activity, diet, and other habits).

• Enhancing Clinical Research: Deep learning helps identify suitable patients for clinical trials, increasing the relevance and efficiency of research. Deep learning models can also quickly identify the impact of treatments on different demographic groups in clinical studies.

4.3. Automatic disease detection and prevention using wearable devices

Wearable devices, such as smartwatches, sensors, and fitness gloves, are becoming increasingly popular tools for monitoring fitness and health. These devices collect data about users, including information on physical activity, stress levels, heart rate, sleep quality, and more. When combined with deep learning techniques, these data can be used to develop systems capable of detecting and preventing diseases.

4.3.1. Automatic Disease Detection

Wearable devices collect various types of data:

• Biometric data: Blood pressure, heart rate, skin temperature, oxygen saturation.

• Activity data: Step count, sleep patterns, physical activity levels.

• Environmental data: Ambient temperature, pollution levels, light.

This data can be analyzed to detect early signs of diseases such as cardiovascular diseases, diabetes, and mental health issues. The system can analyze users' historical data and recommend lifestyle changes, such as physical activity, diet, and stress management. By combining data from multiple sources (wearable devices, mobile apps, electronic health records), the reliability and accuracy of disease detection and prediction models can be improved. This requires technologies for data processing: data fusion (integration of natural language, biometric data, images) and a health ecosystem.

4.4. Potential areas for research and application

Deep learning offers broad opportunities for research and application in disease prediction. The following areas represent research directions that could bring significant benefits to the healthcare industry:

1) Early Disease Detection and Prevention: One of the most promising areas is early cancer detection. Deep learning algorithms analyze medical images (X-rays, MRIs, PET scans), genetic data, and other information to detect cancer signs that are invisible to the human eye. Preventive medicine: Deep learning can predict which patients are at high risk for chronic diseases such as diabetes, cardiovascular diseases, and Alzheimer's disease through data and genetic analysis.

2) Rapidly Evolving Diseases: Deep learning can be key in tracking and predicting outbreaks of infections and epidemics, such as COVID-19. Deep networks use infection spread data to analyze trends and recommend measures to be taken, potentially even predicting new virus variants. It can help respond quickly to emerging diseases like viral infections or unknown pathogens.

3) Improving Medical Imaging: Deep learning can enable more precise and accurate detection of diseases such as cancer, cardiovascular disorders, and stroke. Deep learning models can analyze complex images more quickly and accurately, accelerating treatment and diagnosis.

4) Interpreting Complex Medical Data: Deep learning can analyze various types of data, such as textual medical data, environmental data, and genetic information, providing a better assessment of risks for patients prone to certain diseases.

5) Advances in Drug Discovery: Deep learning is used in drug discovery by analyzing molecular structures and their interactions with potential therapies. It can accelerate the process of discovering drugs that are cheaper, more effective, and with fewer side effects.

6) Support for Fast and Accurate Diagnosis: Deep learning models will be invaluable for diagnosing rare and little-known diseases. By analyzing data from various sources (genetic, clinical, imaging), deep learning models help identify early symptoms of rare diseases, which often remain undiagnosed or misdiagnosed by human experts.

7) Interaction with Robotics and Medical Devices: The future involves integrating deep learning with robotics and medical devices, offering enhanced capabilities for diagnosis, surgery, and rehabilitation.

5. CONCLUSION

This paper explores the development and application of hybrid models and transfer learning in the field of computer science, with a particular focus on their advantages in solving complex problems. Through the analysis of various approaches, it became clear that hybrid models, which combine elements of multiple learning techniques, can significantly improve the accuracy and efficiency of models compared to traditional methods. Transfer learning, as a key component of this technology, enables the transfer of previously acquired knowledge from one domain to another, thereby accelerating the training process and improving the generalization of models, especially in scenarios with limited data.

By examining specific applications of hybrid models and transfer learning, the research demonstrates that these approaches are successfully applied across various industries, including healthcare, the automotive sector, and data analytics, where they provide tangible benefits in terms of reducing errors, enhancing precision, and saving resources. Although these models have shown great potential, further research is needed to optimize their performance and reduce implementation complexity, which presents a challenge for their broader adoption.

In conclusion, the development of hybrid models and transfer learning is crucial for advancing machine learning and artificial intelligence. Despite the challenges, the benefits these approaches offer in addressing real-world problems highlight their immense potential and importance for future technological solutions. Further research in this area can contribute to more efficient resource utilization, better algorithm implementation, and the achievement of advanced results across various industries and research disciplines.

REFERENCES

Alowais, S., Alghamdi, S., Alsuhebany, N., Alqahtani, T., Alshaya, A., Almohareb, S., & Albekairy, A. (2023). Revolutionizing healthcare: the role of artificial intelligence in clinical practice. BMC medical education, 23(1), 689.

Bhambri, P., & Khang, A. (2024). Managing and Monitoring Patient's Healthcare Using AI and IoT Technologies. In Driving Smart Medical Diagnosis Through AI-Powered Technologies and Applications, IGI Global, 1-23.

Bhattacharya, S., Maddikunta, P., Pham, Q., Gadekallu, T., Chowdhary, C., Alazab, M., & Piran, M. (2021). Deep learning and medical image processing for coronavirus (COVID-19) pandemic: A survey. . Sustainable cities and society, 65, 102589.

Dara, S., Dhamercherla, S., Jadav, S., Babu, C., & Ahsan, M. (2022). Machine learning in drug discovery: a review. Artificial intelligence review, 55(3), 1947-1999.

Hider, M., Nasiruddin, M., & Al Mukaddim, A. (2024). Early Disease Detection through Advanced Machine Learning Techniques: A Comprehensive Analysis and Implementation in Healthcare Systems. Revista de Inteligencia Artificial en Medicina, 15(1), 1010-1042.

Johnson, A., Ghassemi, M., Nemati, S., Niehaus, K., Clifton, D., & Clifford, G. (2016). Machine learning and decision support in critical care. Proceedings of the IEEE, 104(2), 444-466.

Kalusivalingam, A., Sharma, A., Patel, N., & Singh, V. (2021). Leveraging Deep Learning and Random Forest Algorithms for AI-Driven Genomics in Personalized Medicine. International Journal of AI and ML, 2(3).

Li, M., Zhang, Y., & Zhu, H. (2023). Medical image analysis using deep learning algorithms. Frontiers in Public Health, 11, 1273253.

Pepe, M., Etzioni, R., Feng, Z., Potter, J., Thompson, M., Thornquist, M., & Yasui, Y. (2001). Phases of biomarker development for early detection of cancer. Journal of the National Cancer Institute, 93(14), 1054-1061.

rabhod, K. (2024). The Role of Artificial Intelligence in Reducing Healthcare Costs and Improving Operational Efficiency. Quarterly Journal of Emerging Technologies and Innovations, 9(2), 47-59.

Vatansever, S., Schlessinger, A., Wacker, D., Kaniskan, H., Jin, J., Zhou, M., & Zhang, B. (2021). Artificial intelligence and machine learning-ided drug discovery in central nervous system diseases: State-of-the-arts and future directions. Medicinal research reviews, 41(3), 1427-1473.

Zhang, B., Shi, H., & Wang, H. (2023). Machine learning and AI in cancer prognosis, prediction, and treatment selection: a critical approach. Journal of multidisciplinary healthcare, 1779-1791.